



- A. \_\_\_\_\_ inches
- B. \_\_\_\_\_ inches
- C. \_\_\_\_\_ inches
- D. \_\_\_\_\_ inches
- E. \_\_\_\_\_ inches
- F. \_\_\_\_\_ inches
- G. \_\_\_\_\_ inches
- H. \_\_\_\_\_ inches
- I. \_\_\_\_\_ inches
- J. \_\_\_\_\_ inches
- K. \_\_\_\_\_ inches
- L. \_\_\_\_\_ inches

**Is O Ring on one side or both?**    One side    Both

**P.S.I. Feed:**    100    225

**Are all discharge holes ported?**    Yes    No

**Center feed hole:**    Tapered    Straight

**Plate Edges:**    Square    Rounded

**Plate Surface:**    Dots    Channels    Bricks

Name: \_\_\_\_\_

Company: \_\_\_\_\_

Email: \_\_\_\_\_

Phone: \_\_\_\_\_

PO Reference: \_\_\_\_\_

Intermediate Cloth Quantity: \_\_\_\_\_

End Cloth Quantity: \_\_\_\_\_

Preferred cloth weave type:    Satin    Oxford

Filter press manufacturer: \_\_\_\_\_

Plate manufacturer: \_\_\_\_\_

Cake thickness: \_\_\_\_\_ in.

Plate thickness: \_\_\_\_\_ in.

Plate width at center eye: \_\_\_\_\_ in.